


**ISO 7010:2011/Amd 7:2016****Graphical symbols - Safety colours and safety signs - Registered safety signs**

....

**Safety sign W041: Warning; Asphyxiating atmosphere**

	<b>Reference No.</b>
	<b>ISO 7010-W041</b>
	<b>Referent</b>
	<b>Warning; Asphyxiating atmosphere</b>
	<b>Function</b> To warn of asphyxiation
	<b>Image content</b> Human figure (right-hand profile) sitting, legs straight, head bent forward and arms hanging, dots around the head and upper body and into the lungs
<b>Hazard</b> Asphyxiation due to exposure to asphyxiating atmosphere	
<b>Human behaviour that is intended to be caused after understanding the safety sign's meaning</b> Taking care to avoid exposure to asphyxiating atmosphere	
<b>Related referents</b> ---	
<b>Additional information</b> Test data obtained according to ISO 9186-1:2014 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

**Dimensioni dei segnali di sicurezza in funzione della distanza di percezione****UNI 7543-1:2004****Colori e segnali di sicurezza - Parte 1: Prescrizioni generali**

Le dimensioni dei segnali di sicurezza devono essere tali che l'area A del segnale e la distanza massima L, dalla quale il segnale deve essere ancora percepibile, soddisfino la relazione:

$$A \geq \frac{L}{2000}$$